



TRE EMME S.p.A.
MANIFATTURA MARCHIGIANA MACERATA
Via Dell'Artigianato, 22
62020 S. ANGELO IN PONTANO (MC) - ITALY
Iscr. Reg. Soc. MC N. 5227 - CCIAA MC N. 100692
Tel. +39 0733.663334/663316/663416 - Fax +39 0733.663417
CAP. SOC. Euro 120.000,00 - P. IVA 00860500438
<http://www.treemme.net> - e-mail: treemme@treemme.net
V.A.T. reg. IT 00860500438

TECHNICAL DATA SHEET

ADHESIVE TAPE: GEKO MSK BASIC

PAPER PROPERTIES

TYPE OF PAPER	IMPREGNATED CREPE PAPER
PAPER THICKNESS (MICRON)	85 (+/-15)
TENSILE STRENGTH MD (N/mm ²)	80 (+/-20)
ELONGATION AT BREAK MD (%)	8 (+/-2)

ADHESIVE PROPERTIES

TYPE OF ADHESIVE	HOT MELT (SOLVENT FREE)
COLOUR	WHITE
PEEL ADHESION (N/25mm)	OVER 6.0

The recommended storage conditions for this product are around 21°C and 50% relative humidity. Prior to use, carefully check that the contact surfaces are totally dry and clean from oil, grease or dust. The data stated above cannot be considered as binding by contract or by specifications. They correspond to the average values obtained from the tests carried out in conformity with AFERA norms. Tests are carried out on samples taken from our standard production. These data may vary without notice – the updated typical value sheet can be forwarded at any time.

Since many different factors influence the product's performance, we recommend testing the product by any application. We remain at your disposal for any further information or recommendations.

01/11/2013